

Slipperiness of the floor tiles vary according to the floor characteristics. Nonslip value is expressed with R.

The tiles with nonslip value between R9 and R13 should be selected according to the use feature of the location.

(STANDARD DIN 51130)

PLACE OF USE	NONSLIP VALUE
Vegetable oil production site	R 13
Oil and solid oil production facility	R 12
Milk industry	R 12
Bakery, patisserie and flour products production site	R 11
Slaughterhouses	R 13
Meat integrated plants	R 13
Chicken products processing sites	R 12
Fishery processing sites	R 13
Vegetable processing sites	R 13
Beverage warehouse	R 10
Beverage filling facility	R 13
Diner, restaurants, mess halls	R 11
Big kitchen (restaurant, hotel, factory)	R 12
Meat and meat products selling area	R 12
Laundry	R 11
Concrete and stone production warehouses	R 11
Automobile repair shops	R 12
Automobile washing areas	R 11
Engine oil and grease oil warehouses	R 12
Treatment plants	R 12
Fire station	R 12
Entrance halls	R 9
Cafeteria, canteen	R 9
Drugstore, hairdresser	R 9
Banks	R 9
Schools (dry areas)	R 9

WARNING: Products with higher than R9 nonslip value (R 10- R11- R 12) are exterior products which have

been produced for use in wet areas. For example; such as poolside. They should never be used in interior locations.

You can get detailed information at our Quality Control department.